



**SCRAIL® DRYWALL**



### SCRAIL® DRYWALL

- The patented thread provides excellent holding power in steel studs ranging from a thickness of 1.0 mm to 2.0 mm (.039" to .078")
- Three longitudinal grooves on the thread ensure controlled displacement of the steel stud material
- Adjustable and removable fastener

### SCRAIL® FACTS

- 8 times faster than bulk screws
- 2 times faster than collated screws
- Driven in at lightning speed
- 80% and more of the holding power of screws
- Adjustable and removable after shot



### CONTACT & SERVICE

Our sales team  
is available at:

P +1 800 239 8665  
sales.us@beck-fastening.com  
www.beck-fastening.com

### DESCRIPTION

The new SCRAIL® DRYWALL nail screw fasteners offer an optimal fastening solution for drywall construction. Their trumpet head and the special STEELTHREAD threading ensure precise and secure mounting of sheetrock and wallboard onto metal and wooden studs. The trumpet head evenly distributes pressure during driving, preventing cracks and breakthroughs in the boards. The result is a smooth, clean surface that allows for easy finishing. In combination with the FASCO® INMOTION hand held carriage and the FASCO® F60 coil nailer, the efficiency and ergonomics in wall prefabrication are significantly improved.

# SCRAIL® DRYWALL

## APPLICATION

- Drywall
- Interior construction
- Manufactured housing
- Millwork

## MATERIAL SPECIFICATIONS

Sheetrock plasterboards and wallboards on light metal (steel thickness 1.2 mm to 1.6 mm) and wooden substructures

## FASTENER DATA

	SCRAIL® DRYWALL
Length	50 / 65 mm   2" / 2.559"
Inner- & Outer diameter	2.8 mm / 3.2 mm   0.110", 0.126"
Collation Type	15° Plastic Sheet Coil
Thread Type	STEELTHREAD
Drive Type	Phillips®
Head	trumpet head
Material	Standard steel electrogalvanized

## COMPATIBLE FASCO® TOOLS

- F60 CN15W-PS90 SCR
- F60 CN15W-PS90 SCR IM

