



## F48A CN15W-45 ROOFING



### TOOL FEATURES

- Straightened adjustment slider permits accurate fastening
- Powerful roofing nailer for 15° wire collated nails
- Patent pending design with excellent ergonomics and tool balance

### BECK ROOFING NAILS

- Large flat head for optimal stability
- For fastening slate shingles and bitumen sheets
- By using the FASCO® coil nailer, the nails can be processed very easily



### CONTACT & SERVICE

Our sales team  
is available at:

T +43 7724 2111-671  
sales@beck-fastening.com  
www.beck-fastening.com

### DESCRIPTION

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- High impact engineered plastic magazine
- Side protectors safeguard tool from contact with rough surfaces
- Contact “Bump” fire trigger for production applications
- Easy change nose plate with carbide inserts keeps tool in position on the roof and protects against abrasion

# F48A CN15W-45 ROOFING

## APPLICATIONS

- Slate shingles
- Bitumen sheets

Especially developed for roofing. It makes working in the height more comfortable and easier.

## HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

Height	Width
270 mm	110 mm
10.63 inch	4.33 inch
Length	Weight
265 mm	3,05 kg
10.43 inch	6.72 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

1.50 L. | 0.053 SCF  
Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

Diameter	3.00 mm   0.118"
Head	10 mm   0.393"
Pitch	8.0 mm   0.314"
Length	19 - 45 mm   ¾" - 1 ¾"
Collation Type	15° Wire Coil Roofing Nails
Capacity	120

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 99.81 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 93.20 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

5.99 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Contact actuation

Loading: Coil

## VARIATIONS

F42 CN15W-45 ROOFING

## FURTHER INFORMATION

### MATERIAL

- Standard steel
- SS304, SS316

### FINISH

- Bright
- Electro-galvanized
- Hot-dipped

### NAIL POINT

- Diamond point

