



**F42 CN15W-45  
ROOFING**

TRANSITION PERIOD: Product branding changes according to the new brand design.

**TOOL  
FEATURES**

- Specially developed for roofing
- Carbide inserts in the nose in order to avoid abrasion and better position the tool
- Adjustable safety and depth regulation

**BECK  
ROOFING NAILS**

- Large flat head for optimal stability
- For fastening slate shingles and bitumen sheets
- By using the FASCO<sup>®</sup> coil nailer, the nails can be processed very easily



**CONTACT & SERVICE**

**Our sales team  
is available at:**

T +43 7724 2111-671  
sales@beck-fastening.com  
www.beck-fastening.com

**DESCRIPTION**

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- High impact engineered plastic magazine
- Side protectors protect the tool from contact with rough surfaces
- Straightened adjustment slider that permits an accurate and smooth fastening of every roof tile
- Single shot and bump fire selector

## APPLICATIONS

- Slate shingles
- Bitumen sheets

Especially developed for roofing. It makes working in the height more comfortable and easier.

## HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry and dirty tool by cleaning and lubricating regularly

## TOOL CHARACTERISTICS

Height	Width
280 mm	110 mm
11.02 inch	4.33 inch
Length	Weight
260 mm	2,35 kg
10.23 inch	5.18 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

0.90 L. | 0.032 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

<b>Diameter</b>	3.00 mm   0.118"
<b>Head</b>	10 mm   0.393"
<b>Pitch</b>	8.0 mm   0.314"
<b>Length</b>	19 - 45 mm   ¾" - 1 ¾"
<b>Collation Type</b>	15° Wire Coil Roofing Nails
<b>Capacity</b>	120

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 97.80 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 85.60 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.89 m/s<sup>2</sup>

## ACTUATION & LOADING

Actuation System:

Single shot & contact actuation

Loading: Coil

## VARIATIONS

F48A CN15W-45 ROOFING

## FURTHER INFORMATION

### MATERIAL

- Standard steel
- SS304, SS316

### FINISH

- Bright
- Electro-galvanized
- Hot-dipped

### NAIL POINT

- Diamond point

