



**F20A GN-50  
LOCK OUT FS**



**TOOL  
FEATURES**

- Full sequential trigger to ensure maximum safety
- Optional available switchable trigger for flexible usage
- Multi-directional exhaust
- Dry firing lock out prevents the tool from working when it's running out of fasteners

**MEDIUM WIRE  
BRADS**

- For GN Brads with 1.02 mm wire diameter (18 Gauge)
- Up to 50 mm length
- Galvanized or stainless steel  
A2 or A4 available



**CONTACT & SERVICE**

**Our sales team  
is available at:**

P +43 7724 2111-671  
sales@beck-fastening.com  
www.beck-fastening.com

**DESCRIPTION**

- Powerful but still very light tool
- Versatile application possibilities in cabinetry and interior construction
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- No-mar tip avoids marking of soft wood
- Quick release nose for easy unjamming
- Slim nose ensures good visibility and precision
- Depth control for precise countersinking

# F20A GN-50 LOCK OUT FS

## APPLICATIONS

- Furniture
- Upholstering
- Kitchen units
- Frame assembly
- Baseboards
- Furring strips
- Boat interiors
- Panels & profiled boards
- Mouldings & decorative trims
- Doors & windows
- Trade shows
- TV & HiFi racks

## HANDLING

1. Load brads from the side into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS

Height	Width
256 mm	60 mm
10.01 inch	2.36 inch
Length	Weight
263 mm	1,38 kg
10.12 inch	3.04 lbs

### Pressure

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

0.53 L. | 0.019 SCF

Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA

Shank	0.039 - 0.050 mm   1.000 - 1.270"
Head	2.20 mm   0.086"
Length	15 - 50 mm 5/8 - 2"
Magazine Capacity	110
Brad Type	GN BRADS (18 GAUGE)

## NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$  : 99.00 dB (A) -  $K_{WA,1s}$  , 2.5

$L_{pA,1s}$  : 86.00 dB (A) -  $K_{pA,1s}$  , 2.5

## VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit  
set by UNI EN ISO 12100-1/2

## ACTUATION & LOADING

Actuation System: Full sequential  
Optional switchable trigger  
(single shot / contact actuation)

Loading: Side Loading

