



**F23A A64-35PB**  
**F23A A64-50PB**



### TOOL FEATURES

- Light weight and powerful tools
- Lock-out, to prevent dry firing
- Removable no-mar tip and extra rubber tip stored

### PINS AND BRADS

- For A64 pins and micro brads with 0.57 mm wire diameter (23 Gauge)
- Up to 35 mm (F23 A64-35PB) or 50 mm length (F23A A64-50PB)
- Galvanized



### CONTACT & SERVICE

Our sales team  
is available at:

P +1 800 239 8665  
sales@beck-america.com  
www.beck-america.com

### DESCRIPTION

- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- No-mar tip avoids marking of soft wood
- Slim nose ensures good visibility and precision

# F23A A64-35PB // F23A A64-50PB

## APPLICATIONS

- Garden furniture
- Upholstering
- Drawer guides
- Case backs
- Kitchen units
- Mouldings and decorative trims
- Sheathing
- Baseboards
- Doors and windows
- Boat interiors
- Shoe making
- Glazing and beading
- Manufactured houses

## HANDLING

1. Load pins or brads from the side into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## TOOL CHARACTERISTICS F23A A64-35PB

Height	Width
200 mm	62 mm
7.87 inch	2.44 inch
Length	Weight
220 mm	1.15 kg
8.66 inch	2.53 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

0.44 L. | 0.016 SCF  
Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA F23A A64-35PB

<b>Diameter</b>	0.64 x 0.64 mm   0.025 x 0.025"
<b>Brads Head</b>	0.87 mm   0.034"
<b>Length</b>	12   15   20   22   25   28   30   32   35 ½   ⅝   ¾   ⅞   1   1 ⅛   1 3/16   1 ¼   1 ⅜
<b>Magazine Capacity</b>	120 pins / brads
<b>Fastener Type</b>	A64 PINS & Micro Brads (23 GAUGE)

## F23A A64-35PB

### NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)  
L<sub>WA,1s</sub> : 83.00 dB (A) - K<sub>WA,1s</sub> , 2.5  
L<sub>pA,1s</sub> : 70.00 dB (A) - K<sub>pA,1s</sub> , 2.5

### VIBRATION VALUE

(UNI ISO/TS 8662-11)  
is below the declaration limit  
set by UNI EN ISO 12100-1/2

### ACTUATION & LOADING

Actuation System: Single Shot  
Loading: Side Loading

## TOOL CHARACTERISTICS F23A A64-50PB

Height	Width
228 mm	62 mm
8.98 inch	2.44 inch
Length	Weight
225 mm	1.23 kg
8.86 inch	2.70 lbs

### Pressure

5 - 7 bar | 70 - 100 psi

### Air consumption per shot

0.50 L. | 0.018 SCF  
Performance at 90 psi | 6.2 bar  
(0.62 MPa)

## FASTENER DATA A23A A64-50PB

<b>Diameter</b>	0.64 x 0.64 mm   0.025 x 0.025"
<b>Brads Head</b>	0.87 mm   0.034"
<b>Length</b>	12   15   20   22   25   28   30   32   35   38   40   45   50 mm ½   ⅝   ¾   ⅞   1   1 ⅛   1 3/16   1 ¼   1 ⅜   1 ½   1 9/16   1 ¾   2"
<b>Capacity</b>	120 brads / pins
<b>Fastener Type</b>	A64 PINS & Micro Brads (23 GAUGE)

## F23A A64-50PB

### NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)  
L<sub>WA,1s</sub> : 87.00 dB (A) - K<sub>WA,1s</sub> , 2.5  
L<sub>pA,1s</sub> : 74.00 dB (A) - K<sub>pA,1s</sub> , 2.5

### VIBRATION VALUE

(UNI ISO/TS 8662-11)  
is below the declaration limit  
set by UNI EN ISO 12100-1/2

### ACTUATION & LOADING

Actuation System: Single Shot  
Loading: Side Loading