



F20A GN-50 LOCK OUT FS



TOOL FEATURES

- Full sequential trigger to ensure maximum safety
- Optional available switchable trigger for flexible usage
- Multi-directional exhaust
- Dry firing lock out prevents the tool from working when it's running out of fasteners

MEDIUM WIRE BRADS

- For GN Brads with 1.02 mm wire diameter (18 Gauge)
- Up to 50 mm length
- Galvanized or stainless steel
A2 or A4 available



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

- Powerful but still very light tool
- Versatile application possibilities in cabinetry and interior construction
- Rubber comfort grip ensures a non-slip handling and reduces vibrations and fatigue
- No-mar tip avoids marking of soft wood
- Quick release nose for easy unjamming
- Slim nose ensures good visibility and precision
- Depth control for precise countersinking

F20A GN-50 LOCK OUT FS

APPLICATIONS

- Furniture
- Upholstering
- Kitchen units
- Frame assembly
- Baseboards
- Furring strips
- Boat interiors
- Panels & profiled boards
- Mouldings & decorative trims
- Doors & windows
- Trade shows
- TV & HiFi racks

HANDLING

1. Load brads from the side into the magazine
2. Connect air supply
3. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
256 mm	60 mm
10.01 inch	2.36 inch
Length	Weight
263 mm	1,38 kg
10.12 inch	3.04 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

0.53 L. | 0.019 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Shank	0.039 - 0.050 mm 1.000 - 1.270"
Head	2.20 mm 0.086"
Length	15 - 50 mm 5/8 - 2"
Magazine Capacity	110
Brad Type	GN BRADS (18 GAUGE)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 99.00 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 86.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

is below the declaration limit
set by UNI EN ISO 12100-1/2

ACTUATION & LOADING

Actuation System: Full sequential

Optional switchable trigger

(single shot / contact actuation)

Loading: Side Loading

